

180 Day Calibration Interval Network enabled toxic gas detection

Information Technology (*IT*) at the component level! A network enabled Gas Sensor Module with the brilliance to provide Sentry, 4-20 mA or Modbus output. This is a stand alone module with the intelligence to provide integral alarms, loaded with features you need. A gas detector with a Sierra Monitor pedigree, Factory Mutual approved and ready to manage your gas risk. The 5100-XX-IT Series provides all the built-in features desired by instrumentation and safety professionals, including:

- FM Approval for performance and safety
- 180 day calibration frequency
- SIL-2 Certified
- Modbus RTU RS-485 interface
- 4-20 mA output
- HART Interface
- SMC Sentry digital bus interface
- ATEX Approved (5100-05-IT)
- IECEx Certified (5100-05-IT)
- Optional Integral alarm relays – Alarm, Warning and Trouble
- Aluminum or 316 Stainless Steel enclosure
- Integral scrolling LED display
- Remote alarm reset
- Optional remote sensor

The 5100-XX-IT can be used as a 4-20 mA component or as a Modbus RTU node. For higher level system capabilities the module can interface directly to Sierra Monitor's Sentry Controller. As part of a Sentry system the user gains capability of system Modbus serial communications, extensive diagnostic features, area and zone alarm management, WebServer interface and multiplexing sensor connections.



O₂
CO
H₂S
Cl₂
ClO₂
SO₂
NO₂
NH₃
HF
HCl



180 Day Calibration Interval

Factory Mutual (FM) Approved for electrical safety and environmental parameters including Class I, Div. 1, Groups B, C, D and Class I, Zone 1, Group IIB+H₂ IP66. The 5100-XX-IT is also SIL Certified and meets NFPA-72 requirements for gas detectors.

How It Works

Electrochemical sensors are fuel cell-like devices consisting of an anode, cathode and electrolyte. The components of the cell are selected so a subject gas, allowed to diffuse into the cell, will cause a chemical reaction and generate a current. The cells are diffusion limited so the rate the gas enters the cell is solely dependent on the gas concentration. The current generated is proportional to the rate of the consumption of the subject gas in the cell.

Features

- ◆ Local scrolling display
- ◆ Non-intrusive calibration, menu driven system
- ◆ FM Approved for performance and hazardous area operation, Class I, Div. 1, Group B, C, D, with NEMA 4X enclosure rated for -40° to 122°F areas
- ◆ Flexible Modbus, 4-20mA, Sentry bus, HART and relay interface
- ◆ SIL-2 Certified

Benefits

- Easy to install in a variety of field applications plus easy to obtain critical safety information wherever needed
- Able to easily and quickly calibrate module without declassifying the area
- For safe and reliable operation in hazardous areas 5100-05-IT also includes FM Approval for performance
- Easy to install in a variety of field applications plus easy to obtain critical safety information wherever needed
- Meets long term reliability design standards

Specifications:

Gas Type	Model	Std. Range ⁽¹⁾	Opt. Max Range	Resolution	Response Time ⁽²⁾	Accuracy	Operating Range		
							°F	°C	RH*
Oxygen	5100-03-IT	5-25 %Vol	25 %Vol	0.1%	<10 sec.	+/- 0.2%	- 4 to 122	-20 to 50	15 – 99%
Carbon Monoxide	5100-04-IT	0-500 PPM	1200 PPM	0.5 PPM	<35 sec.	+/- 1 PPM	- 4 to 122	-20 to 50	15 – 90%
Hydrogen Sulfide	5100-05-IT	0-100 PPM	100 PPM	0.1 PPM	<35 sec.	+/- 3 PPM	- 40 to 122	-40 to 50	15 – 90%
Chlorine	5100-06-IT	0-10 PPM	10.0 PPM	0.1 PPM	<60 sec.	+/- 0.5 PPM	- 4 to 122	-20 to 50	15 – 90%
Chlorine Dioxide	5100-08-IT	0-3 PPM	3.0 PPM	0.1 PPM	<60 sec.	+/- 0.5 PPM	- 4 to 122	-20 to 50	15 – 90%
Sulfur Dioxide	5100-10-IT	0-100 PPM	100 PPM	0.5 PPM	<20 sec.	+/- 0.5 PPM	- 4 to 122	-20 to 50	15 – 90%
Nitrogen Dioxide	5100-12-IT	0-20 PPM	20.0 PPM	0.2 PPM	<35 sec.	+/- 0.5 PPM	- 4 to 122	-20 to 50	15 – 90%
Hydrogen Chloride	5100-21-IT	0-20 PPM	20.0 PPM	0.1 PPM	<100 sec.	+/- 0.1 PPM	- 4 to 122	-20 to 45	15 – 90%
Ammonia	5100-25-IT	0-100 PPM	100 PPM	1.0 PPM	<30 sec.	+/- 1 PPM	+ 14 to 113	-10 to 45	20 – 95%
Hydrogen Fluoride	5100-26-IT	0-10 PPM	10 PPM	0.5 PPM	<30 sec.	+/- 1 PPM	+ 14 to 113	-10 to 45	20 – 95%

(1) Optional ranges available

(2) Response time to 90% full signal value for applied concentration

* = Non-Condensing

Specifications common to all *IT* Toxic Gas Sensor Modules

Sensor type: Electrochemical

Performance
Range: Default range as above
User selectable alternative ranges)

Sensor Life: Typically >2 years

Output:
Display: Fixed and Scrolling LED
Signal Outputs: Sentry digital bus
Analog 4-20 mA
3-wire Non-Isolated
4-wire Isolated
Serial RS-485 Modbus RTU
Optional

Relay :
Options:
Relays: 5 amp Alarm, Warning (0.25 amp Trouble)
5A@ 250 VAC, 5A@ 30VDC (Alarm, Warning)
Board includes auxiliary connection for Sentry multiplexing

HART: Termination board includes HART, Modbus RS-485, 4-20mA, Digital Input, 2A Relay output, No Sentry Bus

Construction:

Dimensions: (HxWxD) (differs for 5100-25-IT & 5100-26-IT)
(A1 & A2) 7.9 x 5.7 x 3.9 in. (20.1 x 14.5 x 9.9 cm)
(S1 & S2) 7.6 x 4.4 x 4.9 in. (19.3 x 11.2 x 12.4 cm)

Weight:
(A1 & A2) 3.4 lb. (1.5 Kg)
(S1 & S2) 7.2 lb. (3.3 Kg)

Housing: Epoxy-coated, die-cast, copper-free Aluminum or 316 Stainless Steel

Rating: Explosion proof, Class 1, Div. I, Groups B, C, D
Group IIB + H2 IP66, IP65, NEMA 4X

Warranty: 2 years

Approvals: FM, CSA for enclosure in hazardous locations
FM Performance Approval (5100-05-IT)
SIL-2 Certified (5100-04-IT, 5100-05-IT, 5100-06-IT)
ATEX Certified II 2 G Ex d IIB+H2 T6 Gb
Ta = -20°C to +50°C (5100-05-IT)
IECEx Certified (5100-05-IT)
CE Mark (5100-05-IT)
ABS (5100-05-IT)
CQST Certified for China (5100-03, -04, & -05 -IT)
CCOE/PESO Certified for India

Specifications subject to change without notice

Power:

Power consumption: 2 watts maximum
Input voltage: 24 VDC nominal: 10-30VDC

Remote Sensor Option: Distance:

5100-03-IT	10 feet
5100-04-IT	15 feet
5100-05-IT	15 feet



Ordering Information:

Model	Gas	Enclosure	Relay/Connection Output	Sensor Protection	Remote Option	ATEX
5100	- XX - 03 = O ₂ - 04 = CO - 05 = H ₂ S - 06 = Cl ₂ - 08 = ClO ₂ - 10 = SO ₂ - 12 = NO ₂ - 21 = HCl - 25 = NH ₃ - 26 = HF	- IT Series - XX - A1 = AL 3/4" NPT - A2 = AL M20 x 1.5 - S1 = SS 3/4" NPT - S2 = SS M20 x 1.5	- XX - 01 = No Relays (std) - 02 = Relays Option - 05 = HART Option	- XX - 0 = Standard - 1 = Conformal Sensor	- X - 0 = None - 1 = Remote Sensor	- X - 0 = Standard - C = ATEX (5100-05-IT only)

Manufactured by



Accessories:

5311-00 Rainshield

5311-02 Rainshield with calibration port

Calibration Accessories:

1250-01 Gas Sensor Calibration Kit, Type A (CO, H₂S)
1250-02 Gas Sensor Calibration Kit, Type B (SO₂, NO₂)
1250-03 Gas Sensor Calibration Kit, Type C (Cl₂, ClO₂)
1260-00 Gas Cylinder, Air, (Type A) 105 Liters
1260-04 Gas Cylinder, CO, 100 PPM, (Type A) 105 Liters
1260-05 Gas Cylinder, H₂S in N₂, 25 PPM, (Type A) 57 Liters
1260-06 Gas Cylinder, Cl₂, 5 PPM, (Type C) 104 Liters

1260-10 Gas Cylinder, SO₂, 50 PPM, (Type B) 74 Liters
1260-12 Gas Cylinder, NO₂, 10 PPM, (Type B) 74 Liters
1260-13 Gas Cylinder, CO, 1000 PPM, (Type A) 105 Liters
1260-21 Gas Cylinder, HCl, 5 PPM, (Type X) 581 Liters
5360-00 Calibration Head, Standard
9210-00 Calibrator, Permeation Type
9211-09 Permeation Tube, Ammonia, NH₃